

Lubrication

Lubrificazione

All unit are supplied with synthetic oil to assure long life lubrication for all mounting positions and maintenance is not necessary. Food grade oil is available on request.

Tutti i riduttori vengono forniti con olio sintetico e lubrificazione tipo "long life" per tutte le posizioni di montaggio e non richiedono manutenzione. Disponibile a richiesta olio alimentare.

FOOD OIL	
Code	Description
LUOFOOD320	Synthetic food oil Foodlube 320' Synthetic food oil Mobil DTE 320'
LUOFOOD150	Synthetic food oil Foodlube 150' Synthetic food oil Mobil DTE 150'

SYNTHETIC OIL	
Code	Description
LUOTVSF320 (Standard)	Synthetic oil 'Telium VSF320' Synthetic oil 'Omala S4 WE320'
LUOBLAS150 (Low temperature)	Synthetic oil 'Blasia S 150' Synthetic oil 'Omala S4 WE150'

VFL

STAINLESS STEEL SHIELDED WORM GEARBOXES

RIDUTTORI A VITE SENZA FINE SCHERMATI IN ACCIAIO INOX

	LD45	LD50	LD63	LD85		
Q.tà	0.08 Lt	0.12 Lt	0.30 Lt	0.95 Lt		

RCL








STAINLESS STEEL SHIELDED RATIO MULTIPLIER

RIDUTTORI COASSIALI AD UNO STADIO SCHERMATI IN ACCIAIO INOX

	411L	511L				
Q.tà	0.10 Lt	0.29 Lt				

STAINLESS STEEL SHIELDED COAXIAL GEARBOXES








RIDUTTORI COASSIALI SCHERMATI IN ACCIAIO INOX

	Standard		On request / A richiesta				
							
	B3	B6	B7	B8	V5	V6	V8
	Life lubricated / Lubrificazione permanente			Oil quantity (Lt) / Quantita (Lt)			
402L	0.25	0.30	0.40	0.40	0.40	0.50	Contact us

BVL

STAINLESS STEEL SHIELDED HELICAL BEVEL GEARBOXES

RIDUTTORI A COPPIA CONICA SCHERMATI IN ACCIAIO INOX

	Standard		On request / A richiesta				
							
	B3	B6	B7	B8	V5	V6	V8
	Life lubricated / Lubrificazione permanente			Oil quantity (Lt) / Quantita (Lt)			
X22L	0.25	0.25	0.25	0.25	0.43	0.31	Contact us
X32L	0.40	0.60	0.40	0.60	0.85	0.60	
X42L	0.60	0.75	0.50	0.70	1.10	0.60	
X52L	0.90	1.50	0.75	1.40	1.95	1.15	
X62L	1.25	1.70	0.95	1.60	2.45	1.50	