

Lubrication

Lubrificazione

STAINLESS STEEL WORM GEARBOXES VFI

RIDUTTORI A VITE SENZA FINE IN ACCIAIO INOX VFI

Unit I30÷I11 are supplied with synthetic oil to assure long life lubrication for all mounting positions and maintenance is not necessary. Food grade oil is available on request.

I riduttori tipo I30÷I11 vengono forniti con olio sintetico e lubrificazione tipo "long life" per tutte le posizioni di montaggio e non richiedono manutenzione. Disponibile a richiesta olio alimentare.

	AGIP Tellium VSF 320			SHELL Omala S4 WE 320		
	I30	I45	I50	I63	I85	I11
Q.tà	0.06 Lt	0.15 / 0.20 Lt	0.22 / 0.28 Lt	0.60 / 0.82 Lt	1.40 / 1.70 Lt	1.60 / 3.50 Lt

Oil plug position - Types

Posizione tappi olio - Tipi

These plugs are on the back side.

Filling & Breather

Filling closed


Emptying

Level




FOOD OIL	
Code	Description
LUOFOOD320	Synthetic food oil Foodlube 320
	Synthetic food oil Mobil DTE 320
LUOFOOD150	Synthetic food oil Foodlube 150
	Synthetic food oil Mobil DTE 150


Standard




Type	I30	I45	I50	I63	I85	I11
Oil q.ty (Lt.)	0.06	0.15	0.22	0.60	1.40	3.50
Std. oil plug 5	F	G	H	H	H	H




Type	I30	I45	I50	I63	I85	I11
Oil q.ty (Lt.)	0.06	0.20	0.28	0.82	1.70	2.50
Std. oil plug 5	F	G	H	H	H	H




Type	I30	I45	I50	I63	I85	I11
Oil q.ty (Lt.)	0.06	0.15	0.22	0.60	1.40	2.50
Std. oil plug 5	F	G	H	H	H	H



Type	I30	I45	I50	I63	I85	I11
Oil q.ty (Lt.)	0.06	0.15	0.22	0.60	1.40	2.10
Std. oil plug 5	F	G	H	H	H	H



Type	I30	I45	I50	I63	I85	I11
Oil q.ty (Lt.)	0.06	0.15	0.22	0.60	1.40	1.60
Std. oil plug 5	F	G	H	H	H	H



Type	I30	I45	I50	I63	I85	I11
Oil q.ty (Lt.)	0.06	0.15	0.22	0.60	1.40	1.60
Std. oil plug 5	F	G	H	H	H	H

On request / A richiesta